

## Auxiliary Device Isolator

Part No. **BF367**



### Overview

- Allows a +24 VDC output from a fire alarm control panel to be remotely isolated to prevent autodiallers, water sprinklers, rollershutters, etc., from activating.
- Designed so that if monitoring is used on the +24 VDC output being controlled, a fault condition will show at the fire panel when the device is Isolated.
- Label includes a white 'write on' area allowing installers to add equipment locations.
- Fits on standard UK 25mm flush or surface mount back boxes.



### More Information

### Technical Specifications

Activation current	10mA @ 27.6 VDC required to illuminate the amber Isolated LED
Indicators	Isolated LED.
Connections	OV; SW In; SW Out.
Product dimensions (mm)	85 W x 85 H x D 19mm.
Construction & finish	White PVC plate; Grey label; Silver plated brass switch material.
IP Rating	IP40.
Weight	TBC.
Operating conditions/temperature	-10°C to +60°C.



Notes

Switching Resistive load 3A @ 30V DC; Switching Inductive load 1.5A @ 30V DC; Non-switching current rating 5A Absolute Max.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom