

HUSH-ACTIV BS 5839-6 Grade C Stand-Alone Domestic Fire Alarm Kit

Part No. HAK/1



Overview

- A Grade C domestic fire detection & alarm system to BS 5839-6 (2019) for use in individual flats, houses and apartments.
- Supplied as a cost-effective kit for ease of specification.
- Includes a Hush-ActiV central controller, a 230V/24V PSU, one ActiV heat detector, one ActiV smoke detector, one ActiV multi-sensor, three ActiV detector bases and an ActiV alarm sounder (additional ActiV devices available for larger systems).
- Monitored for battery, power supply, detector removal & open/short circuit faults.
- Low-level system controller facilitates compliance with the Equality Act.
- Controller includes a replaceable 72 hour standby battery that lasts over 10 years in normal usage.
- Can be used in any situation where Grade D Mains/Battery Alarms are specified.
- A HAK/11 kit is also available with a different mix of fire detectors (one heat, one optical, no multisensor).
- Contact your **C-TEC** account manager for availability details.

More Information

Technical Specifications

Compatible with C-TEC's ActiV range of conventional fire alarm devices. For the contents of this kit, see Compatibility

Kit Contents section below.

Total output current limited to 100mA Battery charge capacity 2Ah. **Quiescent current** 5mA.

Max battery size and type 2Ah Li-Ion battery supplied (replaceable, up to 10 year life).

No. of detector zone circuits No. of conventional sounder circuits 1.

Indicators 4 x LEDs on Hush Controller: Supply (green); Fault (yellow); Alarm (red); Hushed (amber).

Controls 1 x TEST button; 1 x HUSH button.

Yes. Provides audible feedback of a fire/fault condition. Onboard Sounder



T 01942 322744 F 01942 829867

E sales@c-tec.co.uk

W www.c-tec.com



















Hush Controller: 146 W x 85 H x 25 D mm (Can be mounted on a standard UK 35mm double gang flush Product dimensions (mm)

or surface back box).

Construction & finish Supplied on a double gang plastic plate.

IP40. IP Rating Weight 160g.

Operating conditions/temperature -5° C to $+40^{\circ}$ C. Max relative humidity: 95%.

 $Includes\ a\ Hush-ActiV\ central\ controller,\ a\ 230V/24V\ PSU,\ one\ ActiV\ heat\ detector,\ one\ ActiV\ smoke\ detector,\ one\ ActiV\ multi-sensor,\ three\ ActiV\ detector\ bases\ and\ an\ ActiV\ alarm\ sounder.$ Kit contents



















T 01942 322744









